


SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE - SURGE PROTECTION DEVICE

| Type B20 | | |
|---|-----------|----------------------|
| Max. continuous operating voltage | U_C | 255 V AC |
| Lightning impulse current (10/350) | I_{imp} | 20 kA |
| - charge | Q | 10 As |
| - specific energy | W/R | 100 kJ/Ω |
| Temporary overvoltage (TOV) | U_T | 1200 V/0,2 s |
| Nominal discharge current (8/20) | I_n | 20 kA |
| Voltage protection level at I_n | U_p | < 1,3 kV |
| Follow current interrupting rating at U_C | I_{fi} | 100 A _{rms} |
| Response time | t_A | < 100 ns |
| Lifetime | | min. 100 000 h |
| Weight | m | 78 g |
| Article number | | 30 022 |



Gas Discharge Tube

B20



TN-S TT

TYPE 2 CLASS II LPZ 1→2 +80°C / -40°C IP 20 home Industry

